

Declaration of performance

DoP-no. 327/UKCA/2022-11-14

Unique identification code of the product type:
FRAME IC 28 – Fixed and outward opening windows



Intended use:
Domestic and commercial locations

Manufacturer:
Idealcombi A/S,
Noerre Allé 51, 7760 Hurup Thy
Denmark
Phone no. +45 96 88 25 00
E-mail: info@idealcombi.dk

Authorised representative:
n/a

System of AVCP:
System 3

Designated standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Harmonised standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified body:
Danish Technological Institute, NB-no. 1235

Appropriate Technical Documentation and/or Specific Technical Documentation:
n/a

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Hurup, 2022-11-14

Technical Director Mikael Søgaard

Declaration of performance
DoP-no. 327/UKCA/2022-11-14
FRAME IC 28 – Fixed and outward opening windows



Declared performance:

		Resistance to wind load	Watertightness - Non-shielded (A)	Dangerous substances	Load-bearing capacity of safety devices (reversible window)	Acoustic performance	Thermal transmittance, U_w [W/m ² K]	Radiation properties		Air permeability
								Solar factor, g	Light transmittance, τ_v	
Top guided window Single top guided window with std. glazing	Performance	npd	npd	None	-	npd	1.32	0.73	0.82	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						0108/928205			
Side hung window Single side hung window with std. glazing	Performance	npd	npd	None	-	npd	1.32	0.73	0.82	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						0108/928205			
Side guided window Single side guided window with std. glazing	Performance	npd	npd	None	-	npd	1.32	0.73	0.82	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						0108/928205			
Reversible window Single reversible window with std. glazing	Performance	npd	npd	None	350 N, 60 sec.	npd	1.32	0.73	0.82	npd
	Test size [mm]				-		1230 x 1480			
	Notified body				no. 1235		no. 1235			
	Test report no.				0301/631571-TV2		0108/928205			
Fixed sash window Single fixed sash window with std. glazing	Performance	npd	npd	None	-	npd	1.32	0.73	0.82	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						0108/928205			
Fixed light window Single fixed light window with std. glazing	Performance	npd	npd	None	-	npd	1.30	0.73	0.82	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						0108/928205			