

Declaration of performance

DoP-no. 332/UKCA/2022-11-14

Unique identification code of the product type:
NATION IC 48 – Fixed and outward opening windows



Intended use:
Domestic and commercial locations

Manufacturer:
Idealcombi A/S,
Noerre Allé 51, 7760 Hurup Thy
Denmark
Phone no. +45 96 88 25 00
E-mail: info@idealcombi.dk

Authorised representative:
n/a

System of AVCP:
System 3

Designated standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Harmonised standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified body:
Danish Technological Institute, NB-no. 1235

Appropriate Technical Documentation and/or Specific Technical Documentation:
n/a

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Hurup, 2022-11-14

Technical Director Mikael Søgaard

Declaration of performance
DoP-no. 332/UKCA/2022-11-14
NATION IC 48 – Fixed and outward opening windows



Declared performance:

		Resistance to wind load	Watertightness - Non-shielded (A)	Dangerous substances	Load-bearing capacity of safety devices (reversible window)	Acoustic performance	Thermal transmittance, U_w [W/m ² K]	Radiation properties		Air permeability
								Solar factor, g	Light transmittance, τ_v	
Top guided window Single top guided window with std. glazing	Performance	npd	npd	None	-	npd	0.81	0.62	0.75	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						161608			
Side hung window Single side hung window with std. glazing	Performance	npd	npd	None	-	npd	0.81	0.62	0.75	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						161608			
Side guided window Single side guided window with std. glazing	Performance	npd	npd	None	-	npd	0.81	0.62	0.75	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						161608			
Reversible window Single reversible window with std. glazing	Performance	npd	npd	None	350 N, 60 sec.	npd	0.81	0.62	0.75	npd
	Test size [mm]				-		1230 x 1480			
	Notified body				no. 1235		no. 1235			
	Test report no.				0301/631571-TV2		161608			
Fixed sash window Single fixed sash window with std. glazing	Performance	npd	npd	None	-	npd	0.81	0.62	0.75	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						161608			
Fixed light window Single fixed light window with std. glazing	Performance	npd	npd	None	-	npd	0.72	0.62	0.75	npd
	Test size [mm]						1230 x 1480			
	Notified body						no. 1235			
	Test report no.						161608			