

 1235	
Idealcombi A/S Noerre Allé 51, 7760 Hurup Thy Denmark 22 328/UKCA/2022-11-14	
EN 14351-1:2006+A2:2016	
FRAME IC 48 Fixed and outward opening windows Intended for use in domestic and commercial locations	
Resistance to wind load:	npd
Watertightness – Non-shielded(A):	npd
Dangerous substances:	None
Load-bearing capacity of safety devices: (reversible window)	Pass
Acoustic performance:	npd
Thermal transmittance (U_w -value):	
- Single top guided window 1230 x 1480 mm with std. glazing	0.81*
- Single side hung window 1230 x 1480 mm with std. glazing	0.81*
- Single side guided window 1230 x 1480 mm with std. glazing	0.81*
- Single reversible window 1230 x 1480 mm with std. glazing	0.81*
- Single fixed sash window 1230 x 1480 mm with std. glazing	0.81*
- Single fixed light window 1230 x 1480 mm with std. glazing	0.72*
Radiation properties – Solar factor (g):	0.62
Radiation properties – Light transmittance (τ_v):	0.75
Air permeability:	npd
npd: no performance determined	

*Regarding the thermal transmittance of actual windows, we refer to quotations and order confirmations cf. EN 14351-1:2006+A2:2016, Table E.1 note c.