


| | |
|----------------------------------------------------------------------------------------------------------------|-------|
|  1235 | |
| Idealcombi A/S Noerre Allé 51, 7760 Hurup Thy Denmark 22 331/UKCA/2022-11-14 | |
| EN 14351-1:2006+A2:2016 | |
| NATION IC 28 Fixed and outward opening windows Intended for use in domestic and commercial locations | |
| Resistance to wind load: | npd |
| Watertightness – Non-shielded(A): | npd |
| Dangerous substances: | None |
| Load-bearing capacity of safety devices: (reversible window) | Pass |
| Acoustic performance: | npd |
| Thermal transmittance (U_w -value): | |
| - Single top guided window 1230 x 1480 mm with std. glazing | 1.32* |
| - Single side hung window 1230 x 1480 mm with std. glazing | 1.32* |
| - Single side guided window 1230 x 1480 mm with std. glazing | 1.32* |
| - Single reversible window 1230 x 1480 mm with std. glazing | 1.32* |
| - Single fixed sash window 1230 x 1480 mm with std. glazing | 1.32* |
| - Single fixed light window 1230 x 1480 mm with std. glazing | 1.30* |
| Radiation properties – Solar factor (g): | 0.73 |
| Radiation properties – Light transmittance (τ_v): | 0.82 |
| Air permeability: | npd |
| npd: no performance determined | |

*Regarding the thermal transmittance of actual windows, we refer to quotations and order confirmations cf. EN 14351-1:2006+A2:2016, Table E.1 note c.