

**UK  
CA**  
1235

Idealcombi A/S  
Noerre Allé 51, 7760 Hurup Thy  
Denmark

22

341/UKCA/2022-11-14

EN 14351-1:2006+A2:2016

IC Sliding door (28/48)  
Outward opening sliding door

Intended for use in domestic and commercial locations

Resistance to wind load:	npd
Watertightness – Non-shielded(A):	npd
Dangerous substances:	None
Load-bearing capacity of safety devices: (reversible window)	-
Height:	npd
Acoustic performance:	npd
Thermal transmittance ( $U_D$ -value):	
- Single sliding door 2500 x 2180 mm with 2 no. std. glazing	1.18**
Radiation properties – Solar factor (g):	
- Single sliding door, 28 mm glazing sliding part (g):	0.73
- Single sliding door, 48 mm glazing fixed part (g):	0.62
Radiation properties – Light transmittance ( $\tau_v$ ):	
- Single sliding door, 28 mm glazing sliding part ( $\tau_v$ ):	0.82
- Single sliding door, 48 mm glazing fixed part ( $\tau_v$ ):	0.75
Air permeability:	npd

npd: no performance determined

\*\*Regarding the thermal transmittance of actual doors, we refer to quotations and order confirmations cf. EN 14351-1:2006+A2:2016, Table E.2 note d.