

Declaration of performance

DoP-no. 330/UKCA/2022-11-28

Unique identification code of the product type:
FRAME IC 48 – In and outward opening doors



Intended use:
Domestic and commercial locations

Manufacturer:
Idealcombi A/S,
Noerre Allé 51, 7760 Hurup Thy
Denmark
Phone no. +45 96 88 25 00
E-mail: info@idealcombi.dk

Authorised representative:
n/a

System of AVCP:
System 3

Designated standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Harmonised standard:
EN 14351-1:2006 + A2:2016
Windows and doors – Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets

Notified body:
Danish Technological Institute, NB-no. 1235

Appropriate Technical Documentation and/or Specific Technical Documentation:
n/a

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Hurup, 2022-11-28

Technical Director Mikael Søgaard

Declaration of performance
DoP-no. 330/UKCA/2022-11-28
FRAME IC 48 – In and outward opening doors



Declared performance:

		Resistance to wind load	Watertightness - Non-shielded (A)	Dangerous substances	Load-bearing capacity of safety devices (reversible window)	Height	Acoustic performance	Thermal transmittance, U_D [W/m ² K]	Radiation properties		Air permeability
									Solar factor, g	Light transmittance, τ_v	
Glazed door Single inward opening door with 1 no. std. glazing	Performance	npd	npd	None	-	npd	npd	0.91	0.62	0.75	npd
	Test size [mm]							1230 x 2180			
	Notified body							no. 1235			
	Test report no.							161527			
Panelled door Single inward opening panelled door	Performance	npd	npd	None	-	npd	npd	0.73			npd
	Test size [mm]							1230 x 2180			
	Notified body							no. 1235			
	Test report no.							157431			
Enhanced Security Panelled door Single inward opening enhanced security panelled door	Performance	npd	npd	None	-	npd	npd	0.81			npd
	Test size [mm]							1230 x 2180			
	Notified body							no. 1235			
	Test report no.							161527			