


|   |        |
|---|--------|
| <br>1235       |        |
| Idealcombi A/S<br>Noerre Allé 51, 7760 Hurup Thy<br>Denmark<br><br>20<br><br>533/CPR/2020-11-25 |        |
| EN 14351-1:2006+A2:2016   |        |
| External pedestrian doors – Product:<br>NATION IC 28  |        |
| Intended for use in domestic and commercial locations   |        |
| Wind load resistance:   | npd    |
| Watertightness – Non-shielded(A):   | npd    |
| Height:   | npd    |
| Dangerous substances:   | None   |
| Load-bearing capacity of safety devices:  | -      |
| Acoustic performance:   | npd    |
| Thermal transmittance ( $U_D$ -value):  |        |
| - Inward opening door 1230 x 2180 mm with 1 no. std. glazing                                    | 1,34** |
| Radiation properties – Solar factor (g) :   | 0,73   |
| Radiation properties – Light transmittance ( $\tau_v$ ) :                                       | 0,82   |
| Impact resistance:  | npd    |
| Air permeability:   | npd    |
| npd: no performance determined  |        |

\*\*Regarding the thermal transmittance of actual doors, we refer to quotations and order confirmations cf. EN 14351-1:2006+A2:2016, Table E.2 note d.